TS-GCP084-70W-G-50K

LED GARAGE CANOPY



Project Name:	Order Number:	Prepare by:	Note:	Date:	Туре:

70 WATTS

The TS-GCP084-70W-G-50K series

- Fins designed heat sink for better heat dissipation
- Professional light distribution technique, high light reflectivity reflectors
- 155° beam angle
- Light transmission rate of lens is over 90%
- Weather proof













Select color temperature from

• 5000K DAYLIGHT

DIMENSION





TECHNICAL SUMMARY

LUMENS	WATTS	EFFICACY	CRI	VOLTAGE	BEAM °	CCT	PF	LIFE	OPERATING TEMP.	
9100	70W	120 lm/W	80	120V, 277V	155	5000K	>0.9	50,000 hrs	-4°F ~ 104°F	

PART NUMBER ORDERING SUMMARY





www.mwledlighting.com

TS-GCP084-70W-G-50K





Project Name:	Order Number:	Prepare by:	Note:	Date:	Туре:

CONSTRUCTION

 Unit includes heavy duty metal frame, LED array, heat sink and high quality PC lens.

OPTICS

- · Diffuse for uniform illumination.
- · CRI 80+

DRIVER

- 120 277V 60Hz universal input voltage
- 0 -10v smooth flicker free deep dimming to 5%

MOUNTING

- · Ceiling mount
- Surface mount

LISTING

- DLC and UL certified
- EMI/RFI emissions per FCC 47CFR Part 15B.
- Wet location listed

WARRANTY

5 years manufacturer warranty, consult www.mwledlighting.com for more details.

* Terms and conditions may apply.

*5 years limited LED luminaire warranty to the original purchaser that the luminaire shall be free from defects in mate-rials and workmanship from date of shipment, when under properly installed at normal conditions of use. The warranty may not cover physical damage or abuse under certain conditions.

ACCESSORIES (SOLD SEPARATELY)





emergency driver - p83

Motion Sensor - p82