

MRD Square Retrofit Series

4"/6" Baffle or Smooth Retrofit Wattage and Color Selectable



Square Retrofit Downlight

This innovative 4"/6" **Square LED Retrofit Downlight** features **5 selectable color temperatures (2700K–5000K)**, allowing you to customize the ambiance to suit any space. **With a fixed wattage design for consistent performance and reliability, it delivers stable, high-quality illumination for everyday use.** Its distinctive square trim offers a modern and less common alternative to traditional round fixtures, adding a clean architectural touch to ceilings. Designed for quick and easy installation into existing recessed housings, it's a practical and stylish solution for **kitchens, living rooms, bedrooms, hallways, and multi-family residences.**



4"/6" Smooth Retrofit Downlight



4"/6" Baffle Retrofit Downlight


Key Features – Retrofit Downlight

- Modern **square** design for a unique, architectural look
- 5 selectable color temperatures (2700K–5000K)
- Compatible with most standard 4" and 6" recessed housings
- 120V line voltage operation
- Smooth, uniform illumination with reduced glare
- Suitable for damp locations



Baffle/Smooth	4" Retrofit Downlight	6" Retrofit Downlight
Color Temp.	27K/30K/35K/40K/50K	27K/30K/35K/40K/50K
Wattage	11W	14W
Lumens	750LM	1100LM
Voltage	120V	120V
Dimming	TRIAC	TRIAC
CRI	90+	90+

Dimension



Item Number	A(Diameter)	B(Hight)
4" Retrofit Downlight	5"	2.75"
6" Retrofit Downlight	6.75"	3.03"

MRD Square Retrofit Series



4"/6" Baffle or Smooth Retrofit Wattage and Color Selectable

Technical Summary

Item Number	Description	Wattage	Lumens	Color Temp.	Voltage	Dimming	CRI
MSD411SM-5CCT	4" Square Retrofit	11W	750LM	27K/30K/35K/40K/50K	120V	TRIAC	90+
MSD614SM-5CCT	6" Square Retrofit	14W	1100LM	27K/30K/35K/40K/50K	120V	TRIAC	90+

Construction

- Durable die-cast aluminum housing for heat dissipation and long-lasting performance
- Choice of Baffle or Smooth trim in a sleek white finish
- Lightweight, compact design for easy retrofit installation

Driver

- High-efficiency LED driver, compatible with 120V line voltage
- Smooth dimming down to 10%
- Constant current design for stable performance and long life
- Compatible with IC and Non-IC housings

Optics


- 5 selectable color temperatures (2700K–5000K)
- 90+ CRI for accurate color rendering
- Deep-set LED for reduced glare and uniform light distribution
- UV-resistant polycarbonate lens for durability and clarity

Mount

- Fits standard 4" and 6" recessed can housings
- Fits standard 4" and 6" fire rated recessed housings
- Fits 4" remodel housings and 6" remodel housings
- E26 screw base adapter included for easy retrofit
- Quick-install clips for secure, tool-free mounting
- Wet location rated, suitable for bathrooms and covered outdoor ceilings

Accessories (SOLD SEPARATELY)

IC-Type Shallow Housing Can For New Construction



M408-SH (4 inch Shallow Housing)

M608-SH (6 inch Shallow Housing)


IC-Type Shallow Housing Can For Remodeling



M408-SH-RM
(4 inch Shallow Housing Remodel)

M608-SH-RM
(6 inch Shallow Housing Remodel)


Fire Rated Recessed Housing



MF4 (4" Fire Resistant Junction Box)



MFR4-RH (4" Fire Resistant Recessed Housing)



MFR6-RH (6" Fire Resistant Recessed Housing)




MWLIGHTING

MRD Square Retrofit Series

Project Name:	
Prepare By:	
Date:	
Contact/Phone:	


Photometry

4" Square Retrofit Downlight



AVERAGE BEAM ANGLE (50%) 99.7 DEG

6" Square Retrofit Downlight



AVERAGE BEAM ANGLE (50%) 95.9 DEG

Item Number	Description
MSD411SM-5CCT	4" Square Retrofit Downlight
MSD614SM-5CCT	6" 6" Square Retrofit Downlight

Accessories (SOLD SEPARATELY)

Item Number	Description
M408-SH	4 inch Shallow Housing
M608-SH	6 inch Shallow Housing
M408-SH-RM	4 inch Shallow Housing Remodel
M608-SH-RM	6 inch Shallow Housing Remodel
MF4	4" Fire Resistant Junction Box
MFR4-RH	4" Fire Resistant Recessed Housing
MFR6-RH	6" Fire Resistant Recessed Housing