


MHSL Series


Hardscape Light 5CCT

Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

The MHSL Series features a die-cast aluminum housing with an epoxy powder-coated bronze (ORB) finish, a stainless steel mounting bracket, and an optional frosted lens. It is equipped with RGBW (2700K, 3000K, 4000K + RGB) lighting and allows for color temperature selection via a key switch. Designed for efficient installation and energy savings, this series operates on 12-24V AC/DC with a power range of 5W/7W. It utilizes SMD2835 LED technology, offers a Color Rendering Index (CRI) of >90Ra, and delivers luminous outputs of 200LM/280LM with a 120° beam angle. The MHSL Series has a lifespan of 50,000 hours and functions within a temperature range of -4°F to 104°F. Constructed with an aluminum body, a polycarbonate (PC) lens, and a copper cable.



DIMENSION



TECHNICAL SUMMARY

MODEL NO.	WATTS	LUMENS	CCT	VOLTAGE	DIMMING	CRI	CERTIFICATION
MHSL7-5W-5CCT	5W	200LM	27/30/35/40/50K	12-24V	N/A	N/A	ETL
MHSL14-7W-5CCT	7W	280LM	27/30/35/40/50K	12-24V	N/A	N/A	ETL

PART NUMBER ORDERING SUMMARY

MHSL14-7W-5CCT

14" Hardscape Light
MW Lighting

7W
Wattage

27/30/35/40/50K
Selectable CCT



Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

CONSTRUCTION

- Unit includes heavy duty metal frame, LED array, heat sink, hanger, security cable and high quality LED tube.

MOUNTING


- Above Ceiling
- Ceiling Joists & drop ceiling installations

WARRANTY

5 years manufacturer warranty, consult www.mwledlighting.com for more details.

* Terms and conditions may apply.

HIGHLIGHT



Temperature Range

Functions in temperatures from -4°F to 104°F

Durable Construction

Die-cast aluminium housing with epoxy powder-coated bronze (COB) finish and stainless steel mounting bracket