# **MLAS Series**


# 5 CCT Architectural Linear Light

Project Name:	Order Number:	Prepare by:	Note:	Date:	Туре:

The MLAS series offers LED fixtures in three sizes: 2ft, 4ft, and 8ft. The 2ft model is available in 15, 20, and 25-watt options, the 4ft model in 30, 40, and 50 watts, and the 8ft model in 60, 80, and 100 watts. Each fixture has selectable color temperatures of 3000K,3500K, 4000K, 5000K, and 6500K and operates within a voltage range of 120-277V. With a CRI of 80+ and UL listed, it ensures both safety and efficiency for a wide range of applications.



IGHTING





2FT: 610x50x75(mm)/24.01" x1.97" x2.95" 4FT: 1220x50x75(mm)/48.03" x1.97" x2.95" 8FT: 2440x50x75(mm)/96.06" x1.97" x2.95"

**DIMENSION** 

MODEL NO.	WATTAGE	LUMENS	ССТ	VOLTAGE	DIMMING	CRI	CERTIFICATION
MLAS2FT-15/20/25W-5CCT	15/20/25W	1725/2300/2875LM			0-10V	80+	UL
MLAS4FT-30/40/50W-5CCT	30/40/50W	3450/4600/5750LM					
MLAS8FT-60/80/100W-5CCT	60/80/100W	5750/7360/11500LM	30/35/40/50/65K	120-277V			
MLAS2FT-15/20/25W-5CCT-BK	15/20/25W	1725/2300/2875LM		120-2777	0-100	00+	<u>UL</u>
MLAS4FT-30/40/50W-5CCT-BK	30/40/50W	3450/4600/5750LM					
MLAS8FT-60/80/100W-5CCT-BK	60/80/100W	5750/7360/11500LM					





# **MLAS Series**

Project Name: Order Number: Prepare by: Note: Date: Type:	5 CCT Architectural Linear Light					- MWLIGHTING	
	Project Name:	Order Number:	Prepare by:	Note:	Date:	Туре:	

#### **CONSTRUCTION**

 $\cdot$  Unit includes heavy duty metal frame, LED array, heat sink, hanger, security cable and high quality PC lens.

#### **OPTICS**

- Diffuse for uniform illumination.
- CRI 80

### DRIVER

- 120 277V 60Hz universal input voltage
- 0 10v smooth flicker free dimming down to 5%

# MOUNTING

Mount to the ceiling, wall, etc.

## LISTING

• UL 8750 LED equipment in Lighting Products

#### WARRANTY

- 5 years manufacturer warranty, consult www.mwledlighting.com for more details.
- \* Terms and conditions may apply.

\*5 years limited LED luminaire warranty to the original purchaser that the luminaire shall be free from defects in mate-rials and workmanship from date of shipment, when under properly installed at normal conditions of use. The warranty may not cover physical damage or abuse under certain conditions.

### HIGHLIGHT



# Versatile Wattage & Size Option

The MLAS series offers LED fixtures in 2ft, 4ft, and 8ft sizes with multiple wattage choices, ensuring flexibilty for different lighting needs.

### Selectable Color Temperature

Each fixture allows users to choose from 3000K, 3500K, 4000K, 5000K, and 6500K color temperature.

# ACCESSORIES



MLAS-I "I" Joiner



MLAS-SF-KIT Surface Mount Kit



MLAS-L "L" Joiner



MLAS-T "T" Joiner



MLAS-PD-CNPY -(BK) Pendent Mount C anopy and Cable (White/ Black)



MLAS-X "X" Joiner



MLAS-RM-KIT Recessed Mount Kit



MLAS-WM-KIT

Wall Mount Kit