

# MJ-22 Series



## Combo LED Exit/ Emergency Light Universal Single/ Dual Head

Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

This combo COB/SMD LED exit emergency light features an exit sign with optional red or green lettering and dual adjustable heads that rotate 180 degrees. Designed for both quality and reliability, it's built from flame-retardant, impact-resistant thermoplastic, making it ideal for use in humid environments. UL listed, this light provides up to 90 minutes of emergency illumination after a full 24-hour charge.



### DIMENSION



### Technical Summary

MODEL NO.	WATTS	LUMENS	CCT	VOLTAGE	BATTERY	CRI	LED CHIPS
MJ-22	3W	150LM	50K	AC120-277V	built-in 9.6V	80+	12

### PART NUMBER ORDERING SUMMARY

**MJ-22**



# MJ-22 Series



## Combo LED Exit/ Emergency Light Universal Single/ Dual Head

Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

### OPTICS

- Diffuse for uniform illumination.
- CRI 80

### DRIVER

- Built-in 9.6V 700mAH rechargeable Ni-CD battery for minimum 90 minutes emergency operation
- 120/277V voltage operation. Optional multi-tap voltage available.
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.

### MOUNTING

- Universal pattern on back plate for wall mount

### LISTING

- cUL and UL listed for damp location
- UL 8750 LED equipment in Lighting Products

### WARRANTY

- 5 years manufacturer warranty, consult [www.mwledlighting.com](http://www.mwledlighting.com) for more details.
- \* Terms and conditions may apply.

\*5 years limited LED luminaire warranty to the original purchaser that the luminaire shall be free from defects in materials and workmanship from date of shipment, when under properly installed at normal conditions of use. The warranty may not cover physical damage or abuse under certain conditions.

### HIGHLIGHT



#### Universal Design

Single or double face and optional RED/GREEN letters .

#### Durable Design

Flame-retardant, impact-resistant thermoplastic and suitable for use in humid environment